



XBR SERIES XTREME DENSITY BREAKOUT KITS

Opticonx XBR Series Xtreme Density Breakout Kits are designed to provide identification, protection, routing and management to xtreme density cable's high fiber count "round/rollable/spider web" and "flat/oval" ribbons.

Opticonx XBR Series Xtreme Density Breakout Kits route multiple 12 fiber bare ribbons in groups of 12 (144 fibers total) into individual, color coded tubes via protective housing. The color coded, protected, fiber bundles can then be routed to splice trays or even directly terminated with MTP/MPO connectors using Opticonx UBK or UBR Series Breakout Kits.

Features/Benefits

- No special tools required
- Easily identified color coded tubing
- Fits any manufacturer's cable
- Installs in minutes
- Protects and manages bare fiber

Application

1. Ribbon identification, protection, routing and management for mass fusion splicing.
2. Designed specifically to work with Opticonx Xtreme Cassette Module
3. Direct termination of 12 fiber ribbons with MTP/MPO Connectors using Opticonx UBK or UBR Series Breakout Kits



- 1 Body: 114.33mm L x 34.925mm W x 34.925mm D (4.5" x 1.375" x 1.375")
- 2 Terminal: 38.1mm L x 34.925mm W x 34.925mm D (1.5" x 1.375" x 1.375")

Kit components:

Cable body, breakout body, screws and adhesive shrink tubing

Standard tubing length is 2 meters

Custom lengths available

Custom color coded tubing sequences available

For more info, email:

tubingandkits@opticonx.com or

Call 860.821.3222


DESCRIPTION	PART NUMBER
2 x 144 fiber ribbon cable breakout kit	XBR-288
4 x 144 fiber ribbon cable breakout kit	XBR-576
6 x 144 fiber ribbon cable breakout kit	XBR-864
8 x 144 fiber ribbon cable breakout kit	XBR-1152
12 x 144 fiber ribbon cable breakout kit	XBR-1728




THE XD HIGH DEPLOYMENT SOLUTION



The XD patch panel is available in 2, 4, and 6U versions to accommodate any cable, connector or pigtail length for a completely custom solution. Super high density - up to 6,912 fibers in a rack.



The foundation of the XD patch panel is the X+ cassette. It features cable management and is removable. Dust-shuttered VFL LC connectors eliminate the need for dust caps.



The XBR breakout kit is the perfect complement to the XD patch panel for identification, protection, routing and management of 288 to 864 fiber cables.

For more information, call 860.821.3222
or email tubingandkits@opticonx.com