




**Fiber Optic Cable
Furcation Tubing**
PVDF 900uM Furcation Tubing (for 250uM Fiber)



900uM OD x 500uM ID
(0.035" X 0.020")

Part Number:

712000-035XXX

Replace XXX with:

- BLU - BLUE
- ORG - ORANGE
- GREEN - GREEN
- BROWN - BROWN
- GRY - GREY
- WHT - WHITE
- RED - RED
- BLK - BLACK
- YEL - YELLOW
- VIO - VIOLET
- PNK - PINK
- AQU - AQUA



Mechanical:

Diameter: 0.035" (900uM)

Minimum Bend Radius:

2.0" (5cm) Installation

1.2" (3cm) In Service

Cable Weight: 0.35lbs/1000ft (0.52kg/km)

Operating Temperature: -40C to 85C (-40F to 185F)

Storage Temperature: -40C to 85C (-40F to 185F)

Construction

Component

Tube: 0.035" x 0.020" (900uM x 500uM) Flame Retardant Polymer (PVDF)

Tubing Color: To TIA/EIA-359: Blue, Orange, Green, Brown, Grey, White, Red, Black, Yellow, Violet, Pink, Aqua

Applications Note:

This tubing is designed for upjacketing 250um fiber to 900um for direct termination or splicing applications.

www.opticonx.com

Drawn By: PCS
Approved By: PL
Date: 10/10/14
Rev: A

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF Opticonx, Inc. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF Opticonx, Inc. IS PROHIBITED.