




**Fiber Optic Cable
Furcation Tubing
900uM LDPE Tubing**



900uM OD x 500uM ID
(0.035" X 0.020")

Part Number:

782000-035XXX

Replace XXX with:

- BLU - BLUE
- ORG - ORANGE
- GREEN - GREEN
- BROWN - BROWN
- GRY - GREY
- WHT - WHITE
- RED - RED
- BLK - BLACK
- YEL - YELLOW
- VIO - VIOLET
- PNK - PINK
- AQU - AQUA



Mechanical:

Diameter: 0.035" (900uM)

Minimum Bend Radius:

2.0" (5cm) Installation

1.2" (3cm) In Service

Cable Weight: 0.35lbs/1000ft (0.52kg/km)

Operating Temperature: -40C to 85C (-40F to 185F)

Storage Temperature: -40C to 85C (-40F to 185F)

Construction

Component

Tube: 0.035" x 0.020" (900uM x 500uM) Low Density PE
tol. +/- 0.002" (.05mm)

Tubing Color: To TIA/EIA-359: Blue, Orange, Green,
Brown, Grey, White, Red, Black, Yellow, Violet,
Pink, Aqua

Applications Note:

This tubing is designed to upjacket 250um fiber to 900um for
direct termination or splicing applications.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
Opticonx, Inc. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
Opticonx, Inc. IS
PROHIBITED.

www.opticonx.com

Drawn By: PCS
Approved By: PL
Date: 10/10/14
Rev: A