

LIGHT TUBE

900 μ M TUBING FOR 250 μ M FIBER


opticonx
Fiber Optic Cabling Solutions

Opticonx LightTube 900 μ m furcation tubing is a single tube designed for the protection, termination and identification of 250 μ m fiber. Materials include TPE (Hytrel®), Polypropylene (PP), PVDF, Polyethylene (PE) and Nylon. 900x500 is our most common size, but other sizes are available.



Features:

- 16 colors available. 12 colors usually in stock
- Available in these standard lengths:
200, 500, 1000, 1500 meters
- Custom print legend available
- Smooth fiber insertion
- Low shrinkage
- ROHS and REACH compliant
- ITAR compliant
- Made in the USA
- Designed for upjacketing 250 μ m fiber to 900 μ m for direct termination or splicing applications



500 μ m ID x 900 μ m OD
(0.020" x 0.035")

ORDERING INFORMATION

All tubing is available with a pull string and custom print (company name, meter marks, feet marks, phone number, etc)

Part Number	Legacy PN	Material Tube OD x ID mm	Operating Temp	Shrinkage @ 85C	Min Bend Radius	Weight
F09250XX	722000-035XXX	TPE (Hytrel) 900x500 μ m	-40C to +85C	<2%	.5cm Installation	.52kg/km
F09050XX	784000-035XXX	Polypropylene 900x500 μ m	-40C to +85C	<2%	3cm In Service	.52kg/km
F09150XX	712000-035XXX	PVDF 900x500 μ m	-40C to +85C	<2%		.52kg/km
F09350XX	782000-035XXX	Polyethylene 900x500 μ m	-40C to +85C	<2%		.52kg/km
F09450NA	N/A	Nylon 900x500 μ m	-40C to +85C	<2%		.52kg/km

Replace XX with tubing color

NA = Natural
BL = Blue
OR = Orange

GR = Green
BR = Brown
SL = Slate (Gray)

WH = White
RD = Red
BK = Black

YL = Yellow
VI = Violet
PK = Pink

AQ = Aqua
LM = Lime
OL = Olive

MG = Magenta
TN = Tan

TO REQUEST SAMPLES OR A QUOTE, PLEASE EMAIL TUBINGANDKITS@OPTICONX.COM OR CALL 508.499.5013

45 DANCO RD, PUTNAM, CT 06260 | PHONE: 888.748.6855
SITE: WWW.OPTICONX.COM | EMAIL: SALES@OPTICONX.COM

