



# FIBER PRODUCTS FOR 5G/WIRELESS

ENVIRONMENTAL ENCLOSURE FOR 6-24 FIBERS

OPTICONX ENVIRONMENTAL ENCLOSURES ARE DESIGNED TO PROVIDE PROTECTION FOR FIBER-OPTIC CONNECTORS AND SPLICES IN INDOOR OR OUTDOOR ENVIRONMENTS (IP65 RATED). CABLE ACCESS PORTS FEATURE BUILT-IN WEATHER-TIGHT GROMMETS THAT ALLOW FOR EASY CABLE INSTALLATION. NETWORK INTERFACE DEVICES ARE 100% CUSTOMIZABLE FOR YOUR NETWORK - ANY CABLE, ANY CONNECTOR AND ANY LENGTH STUB OR PIGTAIL.

## FEATURES

- Weather-resistant thermoplastic
- IP65 Rated Enclosure, including cable grommets
- Locking Door with Key
- 3 Cable Entry Ports
- Accepts up to 24 Fibers
- 12 Fiber Fusion Splice Tray (Optional)

## APPLICATIONS

- Pre-Wired/Pigtail Configuration: 6 & 12 Fiber
- Pre-Stubbed Configuration - 6, 12, 24 Fiber
- Connector Type: LC/UPC, LC/APC, SC/UPC, SC/APC, MTP/MPO
- Fiber Types: Singlemode & Multimode
- Cable Types: Indoor Premise, OSP, Indoor/Outdoor Rated
- Cable Construction: Stranded Fiber, Ribbon Fiber

## SPECIFICATIONS

- Dimensions: 10" x 7" x 2" (25.9 x 17.7 x 5.1) cm
- Fiber Count: 6/12/24
- Entry Ports: 3
- Splice Tray: 1-12 Fiber
- Material: Weather-resistant thermoplastic

## NOTES

All Opticonx NID enclosures come with cable retention clamp, grid labels & splice sleeves (when configured with fiber pigtails)

## ORDERING INFORMATION

Contact Opticonx customer service for additional configurations.



45 DANCO RD, PUTNAM, CT 06260 | PHONE: 888.748.6855  
WWW.OPTICONX.COM | EMAIL: SALES@OPTICONX.COM